



PORTABLE COLD WATER PRESSURE SYSTEMS

Model	GPM	PSI	HP	Pump	Voltage
P210E	2.1	1000	1.5	General	115 - 1 ph
P315E-1	3	1500	3	General	230 - 1 ph
P411E-1	4	1100	3	General	230 - 1 ph
P411E-3	4	1100	3	General	208 - 3 ph
P411E-3	4	1100	3	General	575 - 3 ph
P419E-1	4	1900	5	General	230 - 1 ph
P419E-3	4	1900	5	General	208 - 3 ph
P419E-3	4	1900	5	General	460/575 - 3 ph
P429E-1	4	2900	7.5	General	230 - 1 ph
P429E-3	4	2900	7.5	General	208 - 3 ph
P429E-3	4	2900	7.5	General	460/575 - 3 ph
P440E-3	4	4000	10	General	208 - 3 ph
P440E-3	4	4000	10	General	460/575 - 3 ph
P562E-1	5.6	2000	7.5	General (belt)	230 - 1 ph
P562E-3	5.6	2000	7.5	General (belt)	208 - 3 ph
P562E-3	5.6	2000	7.5	General (belt)	460/575 - 3 ph
P820E-3*	8	2000	10	General (belt)	208 - 3 ph
P820E-3*	8	2000	10	General (belt)	460/575 - 3 ph
A1 trigger gun activated Start/Stop w/ time delay shutdown (115v/1ph)					
A2 trigger gun activated Start/Stop w/ time delay shutdown (208/220v/1ph)					
A3 trigger gun activated Start/Stop w/ time delay shutdown (208v-575v/3ph)					
* Includes two single lance guns and two 3/8" x 50'					



P210E



P429E3-575V



P325G2



P430G2

PE-Series Electrically Driven -

Includes:

- CSA approval
- Variable pressure lance
- Powder coat painted cart
- Downstream chemical injector
- Thermo Sensor shield
- 50' x 3/8 inch steel braid hose (P210E has 30')
- P315E – 3400 RPM motor - all other system motors are 1750 RPM)
- Trigger gun
- Direct drive pump (unless noted)
- Pneumatic tires

FACTORY ADDED OPTIONS:

- Throttle control automatic engine speed reduction (gasoline driven models)
 - Wet sandblast kit
 - Drain cleaning kit
 - Rotary nozzle / Hose reel
- Special application design with factory consultation

Gas Models	GPM	PSI	HP	Pump	Size
P325G2	3	2500	6.5	General	8 inch
P430G2	4	3000	13	General	10 inch

