

HOSES & ASSEMBLIES



HIGH PRESSURE WASH & CONNECTION HOSES



- 3000 PSI TO 10000 PSI RATED ASSEMBLIES AVAILABLE
- STANDARD, FOOD-GRADE OR STEAM RATED

DRAIN & PIPE CLEANING HOSES



- UP TO 3000 PSI RATED ASSEMBLIES
- IDEAL FOR SMALL DIAMETER DRAIN AND PIPE CLEANING

ST36 SLUDGE SUCTION HOSE



- UP TO 4000 PSI PRESSURE CONNECTION
- 104°F TEMPERATURE RATING

PART NO.	DUTY	INNER DIAMETER	LENGTH	MAX. OPERATING PRESSURE	FITTING SIZE (INCHES)	MAX. TEMPERATURE
206117	PRESS. WASH	3/8 IN.	15 FT.	4000 PSI	3/8 M X 3/8 M	-20° TO 250 °F
200880	PRESS. WASH	3/8 IN.	30 FT.	4000 PSI	3/8 M X 3/8 M	-20° TO 250 °F
200881	PRESS. WASH	3/8 IN.	50 FT.	4000 PSI	3/8 M X 3/8 M	-20° TO 250 °F
206208	PRESS. WASH	3/8 IN.	75 FT.	4000 PSI	3/8 M X 3/8 M	-20° TO 250 °F
200882	PRESS. WASH	3/8 IN.	100 FT.	4000 PSI	3/8 M X 3/8 M	-20° TO 250 °F
202451	PRESS. WASH	3/8 IN.	200 FT.	4000 PSI	3/8 M X 3/8 M	-20° TO 250 °F
202698	PRESS. WASH	1/2 IN.	50 FT.	4000 PSI	3/8 M X 3/8 M	-20° TO 250 °F
200883	PRESS. WASH	1/2 IN.	75 FT.	4000 PSI	1/2 M X 1/2 M	-20° TO 250 °F
401126	PRESS. WASH	1/2 IN.	100 FT.	4000 PSI	1/2 M X 1/2 M	-20° TO 250 °F
202854	PRESS. WASH	1/2 IN.	50 FT.	4000 PSI	1/2 M X 1/2 M	-20° TO 250 °F
206289	STEAM	3/8 IN.	35 FT.	500 PSI	3/8 M X 1/2 M	300 °F
206284	STEAM	1/2 IN.	50 FT.	500 PSI	3/8 M X 1/2 M	300 °F
NOTE: NON-MARKING HOSE COVER , ask for Yellow hose (c/w R&S & Guards)						
207204	PRESS. WASH	3/8 in.	25	3000 psi	3/8 M X 3/8 M	-20° TO 250 °F
206286	PRESS. WASH	3/8 in.	30	3000 psi	3/8 M X 3/8 M	-20° TO 250 °F
206285	PRESS. WASH	3/8 in.	50	3000 psi	3/8 M X 3/8 M	-20° TO 250 °F
207129	PRESS. WASH	3/8 in.	60	3000 psi	3/8 M X 3/8 M	-20° TO 250 °F
206287	PRESS. WASH	3/8 in.	60	3000 psi	3/8 M X 3/8 M	-20° TO 250 °F
NON-MARKING HOSE COVER, BLUE (Food Grade)						
206624	PRESS. WASH	3/8 in.	50	4000 psi	3/8 M X 3/8 M	-20° TO 250 °F
206804	PRESS. WASH	3/8 in.	100	4000 psi	3/8 M X 3/8 M	-20° TO 250 °F
SEWER HOSES						
206717	PRESS. WASH	1/8 in.	50	3000 psi		-20° TO 250 °F
206718	PRESS. WASH	1/8 in.	100	3000 psi		-20° TO 250 °F

HIGH PRESSURE CONNECTION HOSES						
PART NO.	DUTY	INNER DIAMETER	LENGTH	MAX. OPERATING PRESSURE	FITTING SIZE (INCHES)	MAX. TEMP
202520	PRESS.	3/8 IN.	26 IN.	3000 PSI	3/8 M X 3/8 M	250 °F
206112	PRESS.	3/8 IN.	36 IN.	3000 PSI	3/8 M X 3/8 M	250 °F
206110	PRESS.	3/8 IN.	48 IN.	3000 PSI	3/8 M X 3/8 M	250 °F
206113	PRESS.	3/8 IN.	60 IN.	3000 PSI	3/8 M X 3/8 M	250 °F
206119	PRESS.	3/8 IN.	72 IN.	3000 PSI	3/8 M X 3/8 M	250 °F
206152	PRESS.	1/2 IN.	72 IN.	3000 PSI	1/2 M X 1/2 M	250 °F



DRAIN CLEANING & PIPE CLEANING HOSES

PART NO.	DUTY	INNER DIAMETER	LENGTH	MAX. OPERATING PRESSURE	FITTING SIZE (INCHES)
206146	PIPE CLEANING	1/8 IN.	50 FT.	3000 PSI	1/8 M X 1/8 M
206258	PIPE CLEANING	1/8 IN.	100 FT.	3000 PSI	1/8 M X 1/8 M
401200	PIPE CLEANING	1/4 IN.	50 FT.	2750 PSI	1/4 M X 1/4 M
401197	PIPE CLEANING	1/4 IN.	100 FT.	2750 PSI	1/4 M X 1/4 M
DCK1	PIPE CLEANING	1/8 IN.	50 FT.	3000 PSI	1/4 F
DCK2	PIPE CLEANING	1/8 IN.	100 FT.	3000 PSI	1/4 F
DCK3	PIPE CLEANING	1/4 IN.	50 FT.	2750 PSI	1/4 F
DCK4	PIPE CLEANING	1/4 IN.	100 FT.	2750 PSI	1/4 F

SLUDGE SUCTION HOSE - SPECIFY HIGH PRESSURE NOZZLE SIZE WHEN ORDERING

PART NO.	DUTY	INNER DIAMETER	LENGTH	MAX. OPERATING PRESSURE	INLET FITTING	MAX. TEMPERATURE
400136	SLUDGE REMOVAL	1-1/2 IN.	25 FT.	4000 PSI	1/4 IN. M Q.C.	200 °F

IN ADDITION TO THE HOSES SHOWN ABOVE, A FULL RANGE OF HIGH AND LOW PRESSURE HOSES & LENGTHS ARE AVAILABLE FOR VIRTUALLY ANY APPLICATION. CONTACT OUR CUSTOMER SERVICE DEPARTMENT FOR INFORMATION AND PRICING.