



DRAIN CLEANING & PIPE CLEANING HOSES

PART NO.	DUTY	INNER DIAMETER	LENGTH	MAX. OPERATING PRESSURE	FITTING SIZE (INCHES)
206146	PIPE CLEANING	1/8 IN.	50 FT.	3000 PSI	1/8 M X 1/8 M
206258	PIPE CLEANING	1/8 IN.	100 FT.	3000 PSI	1/8 M X 1/8 M
401200	PIPE CLEANING	1/4 IN.	50 FT.	2750 PSI	1/4 M X 1/4 M
401197	PIPE CLEANING	1/4 IN.	100 FT.	2750 PSI	1/4 M X 1/4 M
DCK1	PIPE CLEANING	1/8 IN.	50 FT.	3000 PSI	1/4 F
DCK2	PIPE CLEANING	1/8 IN.	100 FT.	3000 PSI	1/4 F
DCK3	PIPE CLEANING	1/4 IN.	50 FT.	2750 PSI	1/4 F
DCK4	PIPE CLEANING	1/4 IN.	100 FT.	2750 PSI	1/4 F

SLUDGE SUCTION HOSE - SPECIFY HIGH PRESSURE NOZZLE SIZE WHEN ORDERING

PART NO.	DUTY	INNER DIAMETER	LENGTH	MAX. OPERATING PRESSURE	INLET FITTING	MAX. TEMPERATURE
400136	SLUDGE REMOVAL	1-1/2 IN.	25 FT.	4000 PSI	1/4 IN. M Q.C.	200 °F

IN ADDITION TO THE HOSES SHOWN ABOVE, A FULL RANGE OF HIGH AND LOW PRESSURE HOSES & LENGTHS ARE AVAILABLE FOR VIRTUALLY ANY APPLICATION. CONTACT OUR CUSTOMER SERVICE DEPARTMENT FOR INFORMATION AND PRICING.

HOSE REELS



MANUAL REWIND HOSE REELS



* SHOWN WITH
OPTIONAL HOSE AND

HOSE CAPACITY		
MODEL	3/8 IN. I.D. HOSE	1/2 IN. I.D. HOSE
HRA-16	200	175
206288	100	60
200613	200	175

HOSE CAPACITIES MAY VARY
DEPENDING ON HOSE BRAND AND
TYPE

- HRA16 / 403115 - 16 IN. DIAMETER DRUM
- DURABLE POWDER COAT PAINT FINISH
- CAM LEVER BRAKE WITH REEL LOCK
- UP TO 5000 PSI / 300 °F
- INCLUDES UNIVERSAL MOUNTING BRACKET

MANUAL REWIND 360° PIVOTING HOSE REELS



* SHOWN WITH
OPTIONAL HOSE AND

- 206288 - 13 IN. DIAMETER DRUM
- 200613 - 16 IN. DIAMETER DRUM
- DURABLE POWDER COAT PAINT FINISH
- CAM LEVER BRAKE WITH PIVOT & REEL LOCK
- UP TO 5000 PSI / 300 °F
- OPTIONAL 401219 WALL MOUNTING BRACKET AVAILABLE

T SERIES SPRING REWIND HOSE REELS



* SHOWN WITH
OPTIONAL HOSE AND
HOSE STOP

T SERIES - STANDARD		
MODEL	MAXIMUM PRESSURE	HOSE CAPACITY
401568	3000	50' X 3/8" ID
206419	3000	75' X 3/8" ID
401521	4000	50' X 3/8" ID
206542	4000	75' X 3/8" ID

- SUPREME-DUTY REEL WITH ADJUSTABLE GUIDE ARMS, SIX-ROLLER NON-SNAG HOSE GUIDE AND 1 IN. SELF LUBRICATING BEARING
- FULL FLOW SWIVEL JOINT AND 8 POSITION LOCKING RATCHET
- SOLID 1 IN. STEEL CENTRE SUPPORT SHAFT
- DURABLE POWDER COAT PAINT FINISH

MP SERIES SPRING REWIND HOSE REELS - STAINLESS



MP SERIES - STAINLESS STEEL		
MODEL	MAXIMUM PRESSURE	HOSE CAPACITY
206543	3000	50' X 3/8" ID
206544	3000	50' X 1/2" ID

- SUPREME-DUTY REEL WITH ADJUSTABLE GUIDE ARMS, SIX-ROLLER NON-SNAG HOSE GUIDE AND 1 IN. SELF LUBRICATING BEARING
- FULL FLOW SWIVEL JOINT AND 8 POSITION LOCKING RATCHET
- SOLID 1 IN. STEEL CENTRE SUPPORT SHAFT
- 316 STAINLESS STEEL SWIVEL AND AXEL.
- 304 STAINLESS STEEL DRUM AND BASE WITH ELECTROLYTIC POLISH

IN ADDITION TO THE MODELS SHOWN ABOVE, A FULL RANGE OF HIGH AND LOW PRESSURE HOSE REELS IS AVAILABLE FOR VIRTUALLY ANY APPLICATION. CONTACT OUR CUSTOMER SERVICE DEPARTMENT FOR INFORMATION AND PRICING.