

# CONNECTORS & SWIVELS



## QUICK CONNECT PLUGS AND SOCKETS



- (A) ZINC PLATED PLUGS  
NOTE: STAINLESS STEEL AVAILABLE UPON REQUEST
- (B) BRASS SOCKETS WITH BUNA-N O-RING

Q.C. SOCKETS	
PART NO.	THREAD SIZE
209031	1/4 MNPT
209032	1/4 FNPT
209033	3/8 MNPT
209034	3/8 FNPT

Q.C. PLUGS	
PART NO.	THREAD SIZE
209023	1/4 FNPT
209024	1/4 MNPT
209025	3/8 FNPT
209026	3/8 MNPT

O-RINGS FOR SOCKETS	
209079	1/4
209089	3/8

## ST40 SCREW COUPLINGS



- USED WITH ST41 SCREW NIPPLES
- MAXIMUM 5800 PSI OPERATING PRESSURE
- MAXIMUM 300 °F TEMPERATURE RATING

PART NO.	THREAD SIZE
201597	1/4 MNPT
202194	1/4 FNPT
200785	3/8 MNPT
200784	3/8 FNPT

## ST44 SWIVEL COUPLINGS



- MAXIMUM 5.2 GAL/MIN FLOW RATE
- MAXIMUM 5800 PSI OPERATING PRESSURE
- MAXIMUM 300 °F TEMPERATURE RATING

PART NO.	THREAD SIZE
206537	1/4 MNPT
206538	3/8 FNPT

## ST41 SCREW NIPPLES



- USED WITH ST40 SCREW COUPLINGS
- MAXIMUM 5800 PSI OPERATING PRESSURE
- MAXIMUM 300 °F TEMPERATURE RATING

PART NO.	THREAD SIZE
200787	1/4 FNPT
200789	1/4 MNPT
200811	3/8 FNPT
20788	3/8 MNPT

## HIGH PRESSURE SWIVELS




- MAXIMUM 5.2 GAL/MIN FLOW RATE
- MAXIMUM OPERATING PRESSURE: 209085 - 3000 PSI  
209121 - 5000 PSI
- MAXIMUM 300 °F TEMPERATURE RATING

PART NO.	THREAD SIZE
209085	3/8 M X 3/8 F
209121	3/8 M X 3/8 F

# BALL VALVES / BALL VALVE ASSEMBLIES




## 2 WAY BALL VALVES



- BRASS, CARBON STEEL OR STAINLESS STEEL CONSTRUCTION
- UP TO 6000 PSI RATED - HIGHER PRESSURE VALVES AVAILABLE UPON REQUEST

**HIGH PRESSURE RATED**

## CLS / CLS-3 CLEANING STATION ASSEMBLY



PART NO.	MATERIAL		THREAD SIZE-IN.	MAX. PRESS.	MAX. TEMP.	LOCKABLE
	BODY	BALL				
200743	CARBON STEEL	STAINLESS	1/4 F X 1/4 F	2000 PSI	110 °F	NO
400246	STAINLESS	STAINLESS	3/8 F X 3/8 F	2000 PSI	180 °F	YES
220009	STAINLESS	STAINLESS	3/8 F X 3/8 F	6000 PSI	250 °F	NO
200742	CARBON STEEL	STAINLESS	1/2 F X 1/2 F	2000 PSI	110 °F	NO
400247	STAINLESS	STAINLESS	1/2 F X 1/2 F	2000 PSI	180 °F	YES
206535	STAINLESS	STAINLESS	1/2 F X 1/2 F	6000 PSI	250 °F	NO
CLS	STAINLESS	STAINLESS	3/8 F X 3/8 F	2000 PSI	250 °F	NO
CLS-3	STAINLESS	STAINLESS	1/2 F X 1/2 F	6000 PSI	250 °F	NO